


OPTIGRÜN TGF 1.2

Separation and Slip Layer

As a protection and slip layer under drivable layer structures.
Protective layer according to DIN 18531-2.



Material	Recycled PE
Nominal thickness	approx. 1.2 mm
Grammage	approx. 1,200 g/m ²
Colour	black/grey
Quantity/ delivered unit	30 m ² /roll = 2.0 x 15.0 m 1,200 m ² /pallet
Delivery form	40 rolls on disposable pallet = 1,200 m ² disposable pallet 2.05 x 1.30 m
Pack size	according to size of order
Delivery weight	approx. 36.0 kg/roll - approx. 1,465 kg/full disposable pallet

Area of use

- As a protection, separation and slip layer to protection the waterproofing according to DIN 18531-2
- As a second slip layer in conjunction with PE film 0.2 mm under public areas to prevent the transfer of shear and tensile forces
- For the chemically neutral separation of two incompatible materials

Specific properties

- Resistant to bitumen and polystyrene
- Resistant to most chemicals
- Smooth surface
- Ageing resistant, moisture-blocking, and thermally weldable
- UV stabilized

The preceding details are guideline values established under laboratory conditions. These values are subject to a certain manufacturing tolerance. The data contained in this product information sheet represents Optigrün's technical knowledge at the time of publication. Optigrün reserves the right to change and update details in accordance with new insights and to modify specified properties accordingly. No liability accepted for misprints.

Optigrün international AG

Am Birkenstock 15 – 19,
72505 Krauchenwies-Göggingen
Tel. +49 7576 772-0, Fax +49 7576 772-299, info@optigruen.de

Optigreen Limited (Service UK only)

Suite G5 Albany Chambers, 26 Bridge Road East
Welwyn Garden City (Herts), AL7 1HL
Phone +44 203 5899400, Fax +44 207 1171664, info@optigreen.co.uk

